



Dimensions - rolled coil or sheet

Rolled thickness 0.005 - 0.080"

Slit width 0.500 - 9.00"

Density 2.93 g/cm³

Specific Gravity 5.50+/-0.02

Chemical composition

Ag 75.26% nominal

Impurities 0.1% maximum

Appearance:

Translucent, white to silver in color.

Photosensitive, reactive to white light



Common use

Used as cathode material in seawater activated batteries

Note: Can also be supplied in powder/chunk form



+

USA

Attleboro

Umicore Electrical Materials USA, Inc.
527 Pleasant Street, Building 11
Attleboro, MA 02703
Phone: +1 508 838 2064
Fax: +1 508 838 2062
Jay.Burnett@am.Umicore.com

Glens Falls

Umicore Technical Materials North America Inc.
9 Pruy'n's Island Drive
Glens Falls, NY 12801
Phone: +1 732 485 2256
Fax: +1 518-792-3162
Kay.Solecki@am.umicore.com

www.UmicoreElectricalMaterialsUSA.com

The information and statements contained herein are provided free of charge and are for general information purposes only. They are believed to be accurate at the time of publication, but Umicore makes no representations or warranty of any kind with respect thereto, express or implied, about the completeness, accuracy, reliability, suitability or availability. Use or application of such information or statements is at the user's discretion, without any liability on the part of Umicore. Nothing herein shall be constructed as a license or recommendation to use. Umicore reserves the right to alter any product or service at its own discretion. All sales are subject to Umicore's General Terms and Conditions of Sale and Delivery